

SAFETY DATA SHEET

Section 1 – Identification						
Product Name: ASC 1 Base Coat	Manufacturer: American Standard Coatings					
Chemical Name: Acrylic Elastomeric	9631 De Soto Avenue, Chatsworth, CA 91311					
Roof Coating	Information Contacts: (562) 777-8200					
Chemical Family: Acrylic Coatings	Emergency Phone Numbers: US & Canada (800) 535 - 5053					
Product Use: Roof Coating	HMIS Rating: H F R P					
Product #: ASC 1 Gray Base Coat	1 0 0 H					
Section 2 - Hazards Identification						

HEALTH HAZARDS OR RISKS FROM EXPOSURE:

ACUTE:

- **INHALATION:** Breathing excessive vapors or mist may cause nose, throat or lung irritation.
- **INGESTION:** Not an expected route of entry. Ingestion can cause distress to the digestive tract.
- SKIN CONTACT: Prolonged or repeated skin contact can cause irritation.
- EYE CONTACT: Eye contact can cause irritation.

CHRONIC: None known

TARGET ORGANS: ACUTE: Eye, Respiratory System, and Skin. CHRONIC: None Known

CHEMICAL IDENTITY	CAS#	EC Number	Weight %	Hazard Classification
Water	7732-18-5	231-791	35 - 40%	Non Hazard
Acrylic Polymer Emulsion	25852-37-3	Not Listed	23 - 28%	Non Hazard
Titanium Dioxide	13463-67-7	236-675-5	4 - 9%	Non Hazard
Calcium Carbonate	1317-65-3	215-279-6	25 - 30%	Non Hazard
Zinc Oxide Non-Ferrous	1314-13-2	215-222-5	2 - 7%	Non Hazard

First Aid for Eye:

Flush with plenty of water for 15 minutes, including under eyelids. Seek medical attention if discomfort persists. **First Aid for Skin:**

Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water.

First Aid for Inhalation:

Remove to fresh air. If having difficulty, give oxygen. If breathing has stopped, give artificial respiration. Get medical help if discomfort persists.

First Aid for Ingestion:

Seek prompt medical attention IMMEDIATELY.



SAFETY DATA SHEET

FLASH POINT: Not Flammable

AUTOIGNITION TEMPERATURE: Not Applicable

FLAMMABLE LIMITS (in air by volume, %): Lower (LEL): NA Upper (UEL): NA

FIRE EXTINGUISHING MATERIALS: As appropriate for surrounding fire. Carbon dioxide, foam, dry

chemicals, halogen, or water spray.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

This product is non-flammable, however dried product can burn.

Explosion Sensitivity to Mechanical Impact: Not Sensitive.

Explosion Sensitivity to Static Discharge: Not Sensitive.

SPECIAL FIRE-FIGHTING PROCEDURES:

Incipient fire responses should wear eye protection Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and Protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from storm drains, bodies of water, or other environmentally sensitive areas.

Spill or Release

Remove all sources of ignition. Wear appropriate safety equipment as listed in Section 8. Absorb on inert material and dispose in accordance with FEDERAL, STATE and local regulations. Incineration is the preferred method of disposal.

Handling & Storage

Store in well-ventilated area. . Keep containers closed when not in use store away from ignition sources. Store in a clean, dry area.

Other Precautions

All precautions must be observed. Empty container may retain product residue (Solid or liquid).

-----Section 8 - Exposure Controls / Personal Protection------

EXPOSURE LIMITS/GUIDELINES:

MATERIAL	CAS NO.	ACGIH		OSHA
CHEMICAL INGREDIENTS	CAS #	TWA	STEL	TWA
Water	7732-18-5	Not Listed	Not Listed	Non Hazard
Acrylic Polymer Emulsion	25852-37-3	Not Listed	Not Listed	Non Hazard
Titanium Dioxide	13463-67-7	10 mg/m³	-	10 mg/m³
Calcium Carbonate	1317-65-3	10 mg/m ³	-	10 mg/m³
Zinc Oxide Non-Ferrous	1314-13-2	10 mg/m³	-	15 mg/m³



SAFETY DATA SHEET

Personal Protection

- Respiratory Protection Wear an appropriate, properly fitted respirator (NIOSH/MSHA approve during application and handling unless air monitoring demonstrates vapor/ mist levels below applicable limits. Follow respirator manufacturer's recommendations for selection and use.
- Ventilation Sufficient ventilation must be provided to maintain airborne concentrations below TLV, PEL and LEL Limits as listed in section 8.
- Protective Gloves Chemical resistant protective gloves should be worn when handling this product. Check with clove manufacturer to determine proper glove type.
- Eye Protection Splash-proof chemical goggles should be worn.
- Other Protective Equipment Impervious clothing and boots should be worn. Eye bath and safety shower should be provided.
- Hygienic Practices- Good personal hygiene practices are required at all times when handling chemicals. These practices include, but are not limited to, washing when safety equipment is removed, at the end of each shift or when going on breaks and especially if contamination occurs.

BOILING RANGE: 163.4 - 491°F VAPOR DENSITY: Lighter than air. COATING V.O.C.: 11.50 g/l SOLIDS BY WEIGHT: 55.11% SOLUBILITY IN WATER: Complete. APPEARANCE AND ODOR: Typical for water based paints.

SPECIFIC GRAVITY (H₂O=1): 1.29-1.33 EVAPORATION RATE: Slower than the air. MATERIAL V.O.C.: 4.86 g/1 SOILIDS BY VOLUME: 44.52% pH RANGE: 9 +/-5

CONDITIONS TO AVOID

None.

INCOMPATIBILITY (MATERIALS TO AVOID)

Avoid contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

May form toxic materials on thermal decomposition including Carbon Dioxide,

Carbon Monoxide, and various hydrocarbons.

HAZARDOUS POLYMERIZATION:

Will not occur.

TOXICITY DATA:

No LD50 Data Available

SUSPECTED CANCER AGENT:

Ingredients are found on the following lists: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, IARC and therefore it's considered to be, or suspected to be a cancer-causing agent by these agencies. Crystalline Silica

IRRITANCY OF PRODUCT:

Contact with this product can be irritating to exposed skin, eyes and respiratory system.

SENSITIZATION OF PRODUCT:

This product is not considered a sensitizer.



SAFETY DATA SHEET

REPRODUCTIVE TOXICITY INFORMATION:

No information concerning the effects of this product and its components on the human reproductive system.

ENVIRONMENTAL STABILITY:

No Data available at this time.

EFFECT OF MATERIAL ON PLANTS or ANIMALS:

No Data available at this time.

EFFECT OF CHEMICAL ON AQUATIC LIFE:

No Data available at this time.

Dispose of in accordance with all local, state and federal regulations.

US DOT; IATA; IMO; ADR:

THIS PRODUCT IS NOT HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

PROPER SHIPPING NAME: Non-Regulated Material
HAZARD CLASS NUMBER and DESCRIPTION: Not Applicable
UN IDENTIFICATION NUMBER: Not Applicable
PACKING GROUP: Not Applicable.
DOT LABEL(S) REQUIRED: Not Applicable
NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2004): Not Applicable
MARINE POLLUTANT: None of the ingredients are classified by the DOT as a Marine Pollutant (as defined by 49 CFR 172.101, Appendix B)

U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS:

This product is not classified as dangerous goods, per U.S. DOT regulations, under 49 CFR 172.101.

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: This product is not classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA):

This product is not classified as Dangerous Goods, by rules of IATA:

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION:

This product is not classified as Dangerous Goods by the International Maritime Organization.

UNITED STATES REGULATIONS

SARA REPORTING REQUIREMENTS:

This product is not subject to the reporting requirements Of Sections 302, 304 and 313 of Title III of the Superfund

Page 4 of 5



SAFETY DATA SHEET

Amendments and Reauthorization Act., as follows: None TSCA: All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals. SARA 311/312:

Acute Health: YesChronicHealth: NoFire: NoReactivity: No

U.S. SARA THRESHOLD PLANNING QUANTITY:

There are no specific Threshold Planning Quantities for this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb. (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ):

```
None
```

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):

One or more of the ingredients are on the California Proposition 65 lists.

<u>WARNING!</u> This product contains ingredients that are known to the State of California to cause cancer or reproductive harm.

CANADIAN REGULATIONS:

CANADIAN DSL/NDSL INVENTORY STATUS:

All of the components of this product are on the DSL Inventory

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:

No component of this product is on the CEPA First Priorities Substance Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS:

This is not considered to be a hazardous material under the Hazardous Products Act as defined by the Controlled Products Regulations and is therefore not subject

DISCLAIMER

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied regarding its correctness or suitability for consumers intended use and /or application. For this and other reasons, ASC assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If there are any problems or concerns understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.

ASC components are provided as basis without warranties of any kind either expressed or implied. ASC does not warrant the use or the results of use of the materials sold on an as is basis since they are intended for remanufacturing or repackaging. It is the sole responsibility of the user to examine and determine appropriate application and regulatory requirements associated with said ASC components.